


Windy 378 IR

STANDARD EQUIPMENT



- 5.209.0021 Hose 2,5 m 

- 6.205.0126 

- 3.754.0048 

- 3.754.0049 

- 3.754.0083  400 mm

- 3.754.0084 

- 3.754.0085 

- 5.509.2176 Cloth filter 

Optional:

- 5.212.0022 Paper collector filter set - 10 pcs
 - 5.509.1405 Cloth filter for fine dust
 - 5.212.0093 Nylon filter
 - 5.212.0021 Washable filter
 - 5.212.0034 Hepa filter

Equipped with:

- 3 high efficiency by pass motors.
- Suction system with by-pass cooling.
- Filter cleaning system.
- S. S. tank.
- Static electric shock inhibitor.
- Tilting tank.
- Fully removable tank.
- Shock proof trolley.
- Liquid float valve.
- Cloth filter.
- 7,5 m power cable.
- Traceless wheels.
- Accessories Ø 40.
- Handy accessory holder.

Windy 378 IR	
code	8.248.0001
voltage	220-240V ~ 50-60Hz
n°motors - power (max)	3 - 3000 (3600) W High efficiency motor.
column depression	22 kPa/2200 mmH ₂ O
air suction	195 l/s
total volume/dust/liquid	78 l./35 l./48 l.
dimension/weight	62x51x99 cm/26 kg