



STEAM GENERATORS

# SG-20/SG-30

PRESSURE

5 ÷ 5,5  
bar

STEAM FLOW RATE

80 ÷ 100  
g/min

ABSORBED POWER

3  
kW



SG-20

SG-30 - BOILER WITH AUTO-FILLING TANK

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ SUCTION POWER
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ LONG LIFE


MOST FREQUENTLY USE



SPECS



HANDLE FOR A CONVENIENT TRANSPORTATION.



CONTROL PANEL ENSURING A CONSTANT CHECK OF MACHINE MAIN FUNCTIONS.



ROTARY KNOB FOR STEAM QUANTITY CONTROLLER

## TECHNICAL DATA

		<b>SG-20 S 5008 M</b>	<b>SG-30 S 5510 M</b>
Code		GNVA40016	GNVA40017
<b>PERFORMANCE</b>			
Operating pressure	bar/Mpa	5/0,5	5,5/0,55
Steam flow rate	g/min	0-80	0-100
Max steam temperature	°C	140	140
Start up time	min	~ 7	~ 7
Power supply	Ph-V-Hz	1-230-50	1-230-50
Max absorbed power	kW	3	3
Boiler volume	l	2,2	2,2 (auto-filling)
Water tank	l	2	2
Dimension (LxWxH)	cm	57x40x65	57x40x65
Weight	kg	11,5	12

## STANDARD EQUIPMENT

CODE: IPIP45757  
**HANDGRIP + HOSE**  
**STEAM/SUCTION 2,5 m**  
**(FOR SG-20)**



CODE: IPIP40001  
**HANDGRIP + HOSE**  
**STEAM/SUCTION 2,5 m**  
**(FOR SG-30)**



CODE: KTRI46482  
**ACCESSORIES KIT**  
**STEAM/SUCTION**



## OPTIONAL ACCESSORIES

CODE: IPIP47898  
**HANDGRIP + HOSE**  
**STEAM 2,5 m**  
**(FOR SG-20)**



CODE: IPIP45815  
**HANDGRIP + HOSE**  
**STEAM 5 m**  
**(FOR SG-30)**



CODE: KTRI40275  
**STEAM ONLY**  
**ACCESSORIES KIT**



CODE: KTRI89496  
**TROLLEY**



CODE: KTRI40269  
**DESCALING KIT**  
**(10 PHIALS)**

