

STEAM GENERATORS

SG-48 S 8010M

PRESSURE

STEAM FLOW RATE

ABSORBED POWER

3,4 kW

bar

EXCLUSIVE CHARACTERISTICS

- **POWER BOIL**
- **ANTI BUGS**
- **POWER FILTER**
- **SAFETY**
- **ERGONOMICS**
- **POWER FLEX**
- **LONG LIFE**
- **DURABILITY**



MOST FREQUENTLY USE

HO.RE.CA.

FOOD INDUSTRY AND RETAILERS

LARGE COMMON AREAS

SPECS



DIGITAL INDICATOR OF: STEAM TEMPERATURE, STEAM READY AND LACK OF WATER.



STAINLESS STEEL STRUCTURE



5 LITRES DETERGENT AND WATER TANK

TECHNICAL DATA

		SG-48 8010 M
Code		GNVA40043
PERFORMANCE		
Operating pressure	bar/Mpa	8/0,8
Steam flow rate	g/min	100
Steam temperature (max)	°C	180
Start up time	min	~ 5
Power supply	Ph-V-Hz	1-230-50
Absorbed power max.	kW	3,4
Vacuum power	kW	1,2
Boiler volume	l	3,5
Water tank	l	5
Dimension (LxWxH)	cm	74x51x104

STANDARD EQUIPMENT

CODE: IPIP40012

HANDGRIP + HOSE 4 m

Weight



CODE: MPVR40958 HOSE EXTENSION L=500 mm 2 PZ

Kg



CODE: SPPV40060
MULTIPURPOSE FLOOR
BRUSH



CODE: SPPV40061

CARPET PROTECTION FOR

MULTIPURPOSE BRUSH

34

CODE: SPPV40062
FRAME WITH BRISTLES AND
RUBBER SCRAPERS FOR
MULTIPURPOSE BRUSH



CODE: SPPV40063
GLASS CLEANER











CODE: SPPV40056

ROUND BRUSH POLYESTER
BRISTLE Ø28 mm



CODE: SPPV40068

ROUND BRUSH POLYESTER
BRISTLE Ø65 mm



CODE: SPPV40069
ROUND BRUSH POLYESTER
BRISTLE Ø40 mm



CODE: SPPV40070
ROUND BRUSH INOX
BRISTLE Ø40 mm



CODE: AZMC40024
KEY FOR MAINTENANCE



CODE: SPPV40058
RECTANGULAR CLOTH







